

BOGE Model	Max. pressure		Effective free air delivery* 50 Hz		Effective free air delivery* 60 Hz		Motor power		Dimensions B x T x H mm	Weight kg
	bar	psig	m³/min	cfm	m³/min	cfm	kW	HP		
C 10 L	8	115	1,100	38	1,07	37	7,5	10,0	1171 x 599 x 595	260
C 10 L	10	150	1,060	37	1,03	36	7,5	10,0	1171 x 599 x 595	260
C 15 L	8	115	1,770	62	–	–	11,0	15,0	1333 x 599 x 606	290
C 15 L	10	150	1,700	60	–	–	11,0	15,0	1333 x 599 x 606	290
C 20 L	8	115	2,280	80	2,21	78	15,0	20,0	1333 x 599 x 606	300
C 20 L	10	150	2,240	79	2,17	76	15,0	20,0	1333 x 599 x 606	300

\* Free air delivery figures in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure. Emitted sound pressure levels from 68 dB(A) according to DIN EN ISO 2151:2009

BOGE Model	Max. pressure		Receiver volume Litres	Effective free air delivery* 50 Hz		Effective free air delivery* 60 Hz		Motor power		Receiver option Litres	Dimensions B x T x H mm	Weight kg
	bar	psig		m³/min	cfm	m³/min	cfm	kW	HP			
C 10 LR	8	115	350	1.100	38	1.07	37	7.5	10.0	500	1729 x 620 x 1229	370
C 10 LR	10	150	350	1.060	37	1.03	36	7.5	10.0	500	1730 x 620 x 1229	370
C 15 LR	8	115	350	1.770	62	–	–	11.0	15.0	500	1731 x 620 x 1229	410
C 15 LR	10	150	350	1.700	60	–	–	11.0	15.0	500	1732 x 620 x 1229	410
C 20 LR	8	115	350	2.280	80	2.21	78	15.0	20.0	500	1733 x 620 x 1229	430
C 20 LR	10	150	350	2.240	79	2.17	76	15.0	20.0	500	1734 x 620 x 1229	430

\* Free air delivery figures in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure. Emitted sound pressure levels from 68 dB(A) according to DIN EN ISO 2151:2009

BOGE Model	Max. pressure**		Receiver volume Litres	Effective free air delivery* 50 Hz		Effective free air delivery* 60 Hz		Motor power		Dimensions B x T x H mm	Weight kg
	bar	psig		m³/min	cfm	m³/min	cfm	kW	HP		
C 10 LDR	8	115	350	1.100	38	1.07	37	7.5	10.0	1814 x 620 x 1282	400
C 10 LDR	10	150	350	1.060	37	1.03	36	7.5	10.0	1815 x 620 x 1282	400
C 15 LDR	8	115	350	1.770	62	–	–	11.0	15.0	1813 x 620 x 1282	440
C 15 LDR	10	150	350	1.700	60	–	–	11.0	15.0	1814 x 620 x 1282	440
C 20 LDR	8	115	350	2.280	80	2.21	78	15.0	20.0	1813 x 620 x 1282	460
C 20 LDR	10	150	350	2.240	79	2.17	76	15.0	20.0	1814 x 620 x 1282	460

\* Free air delivery figures in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure. Emitted sound pressure levels from 68 dB(A) according to DIN EN ISO 2151:2009

\*\* Max. pressure of the compressor